

# Product Data Sheet

## Skykleen® 2000

### Application/Uses

- Adhesive/Epoxy Removal
- Carbon Epoxy Composite Surface Cleaning
- Carbon Removal (Brake and Piston Housings)
- Degreasing
- Engine Cleaning
- Fiberglass Resin Removal
- Final Cleaning prior to Painting and Bonding
- General Surface Cleaning
- Polysulfide Sealant Removal (Cured/Uncured)
- RTV Removal
- Skydrol Removal

### Product Description

Skykleen 2000 is a new generation aviation solvent that combines excellent cleaning performance with environmentally friendly characteristics.

### Typical Properties

Property	Typical Value, Units
Appearance	Cloudy, white paste
Autoignition Temperature	438°C (820°F)
Density	9.06 lb/gal
Distillation range	200-220°C (392-428°F)
Fire Point	118°C (244°F)
Flash Point	102°C (216°F)
Freezing Point	-40°C (-40°F)
Odor	Low
Solubility in Water	Contains approx. 9% insolubles

*Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.*

