

Product Data

BP Turbo Oil 2380

Balanced All-around Performance

Description

- BP Turbo Oil 2380 is a 5 cSt synthetic lubricant that is approved against US military specification MIL-PRF-23699 STD, and UK military specification DEF STAN 91-101 (replaced DERD 2499).
- This lubricant provides a balanced combination of thermal and oxidation stability, load carrying capacity, lower volatility and has the best low temperature flow characteristics of all 5 cSt turbine oils.

Application

BP Turbo Oil 2380 is recommended for the lubrication of most fixed wing and rotary wing aircraft gas turbines and accessories. It is also recommended for the lubrication of aero-derived gas turbines in industrial power generation, offshore and marine applications.

BP Turbo Oil 2380 has been approved by a wide range of engine and accessory manufacturers for their applicable equipment, including:

Rolls-Royce, GE, Pratt & Whitney, Pratt & Whitney Canada, Pratt & Whitney Aero Power APUs (formally Hamilton Sundstrand), United Technologies Aerospace Systems (formally Hamilton Sundstrand), Honeywell, CFMI, IAE, MTU and Turbomeca.

The wide range of approvals make it an ideal single oil solution for many aircraft. Please contact our local representatives shown in the Eastman Aviation Solutions website for approval details.

Advantages

- BP Turbo Oil 2380 has the best low temperature viscosity properties among all 5 cSt oils.
- Minimum formation of varnish and sludge deposits over long periods of use.
- Very benign to commonly used seal materials in gas turbines.
- BP Turbo Oil 2380 is among the best of its class and provides excellent protection to bearings, gears, and other highly loaded lubricated surfaces.
- Its high degree of oxidation resistance permits a long period of operation without significant increase in viscosity and/or total acidity.

Storage

- The shelf life of BP Turbo Oil 2380 can extend beyond four years when stored in original, unopened quart cans under recommended storage conditions, i.e. in a well-ventilated and covered area away from extreme heat and moisture etc. 55-gallon drums and 5-gallon pails have an expected shelf life of three years minimum.
- For all package styles, shelf life can be increased significantly beyond those stated above, depending upon storage conditions.

Please contact your Eastman representative if you have any questions about product usability.

Typical Characteristics

Name	Method	Units	BP Turbo Oil 2380
Density @ 15°C	ASTM D1298	Kg/l	0.9749
Kinematic Viscosity @ 100°C	ASTM D445	mm ² /s	4.97
Kinematic Viscosity @ 40°C	ASTM D445	mm ² /s	24.2
Kinematic Viscosity @ -40°C after 35 minutes	ASTM D2532	mm ² /s	7,950
Pour Point	ASTM D97	°C	-57
Flash Point	ASTM D92	°C	265
Total Acid Number	SAE ARP5088	mgKOH/g	0.43
Evaporation Loss (6.5 hrs @ 204°C)	ASTM D972	%	3.0
Foaming Characteristics			
Sequence 1 @ 24°C	ASTM D892	ml/vol	9/0
Sequence 2 @ 93 °C			8/0
Sequence 3 @ 24°C			8/0
Load Carrying Ability, IAE Gear Machine, Ref Oil A			
2000rpm	IP 166	%	99
6000rpm			86
Rubber Swell			
Nitrile Rubber (192 hrs @ 130°C)	DERD Test, Method 4	%	10.5
Viton Rubber (192 hrs @ 200°C)			22.5
Silicone Rubber (192 hrs @ 175°C)			10.5
Viton LCS Rubber (192 hrs @ 200°C)			14

BP Turbo Oil 2380
2014

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of their suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

©2014 Eastman Chemical Company. Eastman Aviation Solutions is a trademark of Eastman Chemical Company. BP is a trademark of British Petroleum Company Ltd. Eastman Chemical Company is licensed to use these marks in the marketing of BP Turbo Oil and BP HALO products. The ® used herein denotes registered trademark status in the US; marks referenced herein may also be registered internationally.

For the sales or technical contact nearest you, please visit the BP Turbo Oil page on www.EastmanAviationSolutions.com or send an email to TurboOil@eastman.com.